

# Indexer lubrication

### Oil lubrication

The indexer is supplied with the synthetic lubricating oil Klübersynth GHE 6 - 460 as standard. It is lubricated for life and, accordingly, an oil change should only be carried out if the condition of the oil changes significantly compared to the original condition. The oil level should be checked at regular intervals. It is sufficient if oil is visible in the sight glass when the indexer is at a standstill. This ensures the lubrication of cam followers and cam.

At speeds below 150 rpm
Klübersynth GHE 6 – 460
Mobile Glygoyle HE 460 [ISO V6 460]
Shell Omala S4 WE 460

At speeds higher 150 rpm
Klübersynth GHE 6 – 100
Mobile Glygoyle 22 [ISO V6 150]
Shell Omala S4 WE 150



## Attention

Never mix different types of oil!



## Attention

Only top up the lubricant mentioned above!

When filled with food oil NSF H1 registered - in accordance with FDA 21 CFR § 178.3570, the gear unit is delivered with Klübersynth UH1 6 - 460.

It is lubricated for life and, accordingly, an oil change should only be carried out if the condition of the oil changes significantly compared to the original condition. The oil level should be checked at regular intervals. It is sufficient if oil is visible in the sight glass when the indexer is at a standstill. This ensures the lubrication of cam followers and cam.

At sp	peeds	below	150	rpm

Klübersynth UH16 – 460

At speeds higher 150 rpm

Klübersynth UH1 6 – 150



## Attention

Never mix different types of oil!



Only top up the lubricant mentioned above!

### **Grease Iubrication**

It is lubricated for life and, accordingly, a grease change should only be carried out if the condition of the grease changes significantly compared to the original condition.

usual grease lubrication
TRIBOL GROO
Microlube GB 00

NSF H1 registered, conforms to FDA 21 CFR § 178.3570
Klüberfood NH1 94-6000
Klübersynth UH1 14-1600



## Attention

Never mix different types of grease!



#### Attention

Only top up the lubricant mentioned above!

LILIENTHALSTRASSE 21 – 64625 BENSHEIM PHONE: +49 (0) 6251 / 1069 -0 MAIL: mail@heinz.gmbh